

**IB03 - Cesium Chloride 1% Cs, Ionization Buffer**

## Safety Data Sheet

According to U.S.A. Federal Hazcom 2012

### 1. Identification

**1.1. Product identifier**

Code:

**IB03**

Product name

**Cesium Chloride 1% Cs, Ionization Buffer****1.2. Relevant identified uses of the substance or mixture and uses advised against**

Intended use

**For laboratory use only.****1.3. Details of the supplier of the safety data sheet**

Name

**EXAXOL CHEMICAL CORPORATION**

Full address

**14325 60 TH ST N**

District and Country

**33760 CLEARWATER - FLORIDA****US****Tel. 1-727-524-7732****Fax 1-727-532-8221**

e-mail address

**info@exaxol.com****1.4. Emergency telephone number**

For urgent inquiries refer to

**1-800-255-3924****ChemTel Inc.**

### 2. Hazards identification

**2.1. Classification of the substance or mixture**

The product is classified as hazardous pursuant to the provisions set forth in OSHA Hazard Communication Standard (HCS) (29 CFR 1910.1200). The product thus requires a safety datasheet.

Any additional information concerning the risks for health and/or the environment are given in sections 11 and 12 of this sheet.

## Classification and Hazard Statement

## Hazard pictograms:

Reproductive toxicity, category 2

Suspected of  
damaging fertility or  
the unborn child.

Eye irritation, category 2

Causes serious eye  
irritation.

Skin irritation, category 2

Causes skin irritation.

**IB03 - Cesium Chloride 1% Cs, Ionization Buffer**

Signal words:

Warning

Hazard statements:

**H361** Suspected of damaging fertility or the unborn child.  
**H319** Causes serious eye irritation.  
**H315** Causes skin irritation.

Precautionary statements:

Prevention:

**P202** Do not handle until all safety precautions have been read and understood.  
**P201** Obtain special instructions before use.  
**P280** Wear protective gloves/ protective clothing / eye protection / face protection.  
**P264** Wash skin thoroughly after handling.

Response:

**P305+P351+P338** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
**P308+P313** IF exposed or concerned: Get medical advice / attention.  
**P332+P313** If skin irritation occurs: Get medical advice / attention.  
**P337+P313** If eye irritation persists: Get medical advice / attention.  
**P302+P352** IF ON SKIN: wash with plenty of water.  
**P362+P364** Take off contaminated clothing and wash it before reuse.

Storage:

**P405** Store locked up.

Disposal:

**P501** Dispose of contents / container to an approved waste disposal plant.

**2.2. Other hazards**

Information not available

**3. Composition/information on ingredients****3.2. Mixtures**

Contains:

| Identification           | x = Conc. %      | Classification:                                                                                                                                                                                     |
|--------------------------|------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>WATER</b>             |                  |                                                                                                                                                                                                     |
| CAS 7732-18-5            | $95 \leq x < 97$ |                                                                                                                                                                                                     |
| EC 231-791-2             |                  |                                                                                                                                                                                                     |
| INDEX -                  |                  |                                                                                                                                                                                                     |
| <b>Hydrochloric Acid</b> |                  |                                                                                                                                                                                                     |
| CAS 7647-01-0            | $2 \leq x < 2,5$ | Substance or mixture corrosive to metals, category 1 H290, Skin corrosion, category 1B H314, Serious eye damage, category 1 H318, Specific target organ toxicity - single exposure, category 3 H335 |
| EC 231-595-7             |                  |                                                                                                                                                                                                     |

**IB03 - Cesium Chloride 1% Cs, Ionization Buffer**

INDEX -

**Cesium Chloride**

CAS 7647-17-8

 $1 \leq x < 1,5$ 

Reproductive toxicity, category 2 H361

EC 231-600-2

INDEX -

The full wording of hazard (H) phrases is given in section 16 of the sheet.

**4. First-aid measures****4.1. Description of first aid measures**

EYES: Remove contact lenses, if present. Wash immediately with plenty of water for at least 30-60 minutes, opening the eyelids fully. Get medical advice/attention.

SKIN: Remove contaminated clothing. Rinse skin with a shower immediately. Get medical advice/attention.

INGESTION: Have the subject drink as much water as possible. Get medical advice/attention. Do not induce vomiting unless explicitly authorised by a doctor.

INHALATION: Get medical advice/attention immediately. Remove victim to fresh air, away from the accident scene. If the subject stops breathing, administer artificial respiration. Take suitable precautions for rescue workers.

**4.2. Most important symptoms and effects, both acute and delayed**

Specific information on symptoms and effects caused by the product are unknown.

**4.3. Indication of any immediate medical attention and special treatment needed**

Information not available

**5. Fire-fighting measures****5.1. Extinguishing media****SUITABLE EXTINGUISHING EQUIPMENT**

The extinguishing equipment should be of the conventional kind: carbon dioxide, foam, powder and water spray.

**UNSUITABLE EXTINGUISHING EQUIPMENT**

None in particular.

**5.2. Special hazards arising from the substance or mixture****HAZARDS CAUSED BY EXPOSURE IN THE EVENT OF FIRE**

Do not breathe combustion products.

**5.3. Advice for firefighters****GENERAL INFORMATION**

Use jets of water to cool the containers to prevent product decomposition and the development of substances potentially hazardous for health. Always wear full fire prevention gear. Collect extinguishing water to prevent it from draining into the sewer system. Dispose of contaminated water used for extinction and the remains of the fire according to applicable regulations.

**SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS**

Normal fire fighting clothing i.e. fire kit (BS EN 469), gloves (BS EN 659) and boots (HO specification A29 and A30) in combination with self-contained open circuit positive pressure compressed air breathing apparatus (BS EN 137).

## IB03 - Cesium Chloride 1% Cs, Ionization Buffer

## 6. Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Block the leakage if there is no hazard.

Wear suitable protective equipment (including personal protective equipment referred to under Section 8 of the safety data sheet) to prevent any contamination of skin, eyes and personal clothing. These indications apply for both processing staff and those involved in emergency procedures.

### 6.2. Environmental precautions

The product must not penetrate into the sewer system or come into contact with surface water or ground water.

### 6.3. Methods and material for containment and cleaning up

Collect the leaked product into a suitable container. Evaluate the compatibility of the container to be used, by checking section 10. Absorb the remainder with inert absorbent material.

Make sure the leakage site is well aired. Contaminated material should be disposed of in compliance with the provisions set forth in point 13.

### 6.4. Reference to other sections

Any information on personal protection and disposal is given in sections 8 and 13.

## 7. Handling and storage

### 7.1. Precautions for safe handling

Ensure that there is an adequate earthing system for the equipment and personnel. Avoid contact with eyes and skin. Do not breathe powders, vapours or mists. Do not eat, drink or smoke during use. Wash hands after use. Avoid leakage of the product into the environment.

### 7.2. Conditions for safe storage, including any incompatibilities

Store only in the original container. Store in a ventilated and dry place, far away from sources of ignition. Keep containers well sealed. Keep the product in clearly labelled containers. Avoid overheating. Avoid violent blows. Keep containers away from any incompatible materials, see section 10 for details.

### 7.3. Specific end use(s)

Information not available

## 8. Exposure controls/personal protection

### 8.1. Control parameters

Regulatory References:

|     |              |                                                                                                                                                                                                                                                |
|-----|--------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| USA | NIOSH-REL    | NIOSH publication No. 2005-149, 3th printing, 2007.<br>Occupational Exposure Limits - Limits for Air Contaminants TABLE Z-1-1910.1000.<br>California Division of Occupational Safety and Health (Cal-OSHA) Permissible Exposure Limits (PELs). |
| USA | OSHA-PEL     |                                                                                                                                                                                                                                                |
| USA | CAL/OSHA-PEL |                                                                                                                                                                                                                                                |

#### Hydrochloric Acid Threshold Limit Value

| Type | Country | TWA/8h |     | STEL/15min |       |
|------|---------|--------|-----|------------|-------|
|      |         | mg/m3  | ppm | mg/m3      | ppm   |
| OSHA | USA     |        |     | 7 (C)      | 5 (C) |

|                                                 |  |  |  |                      |
|-------------------------------------------------|--|--|--|----------------------|
| EXAXOL CHEMICAL CORPORATION                     |  |  |  | Revision nr. 1       |
|                                                 |  |  |  | Dated 9/25/2025      |
|                                                 |  |  |  | First compilation    |
| IB03 - Cesium Chloride 1% Cs, Ionization Buffer |  |  |  | Printed on 9/25/2025 |
|                                                 |  |  |  | Page n. 5/13         |

|          |     |   |       |       |
|----------|-----|---|-------|-------|
| CAL/OSHA | USA | 7 | 5     |       |
| NIOSH    | USA |   | 7 (C) | 5 (C) |

Legend:

(C) = CEILING ; INHAL = Inhalable Fraction ; RESP = Respirable Fraction ; THORA = Thoracic Fraction.

8.2. Exposure controls

As the use of adequate technical equipment must always take priority over personal protective equipment, make sure that the workplace is well aired through effective local aspiration. Personal protective equipment must comply with current regulations.

HAND PROTECTION

Protect hands with category III work gloves (OSHA 29 CFR 1910.138).  
The following should be considered when choosing work glove material: compatibility, degradation, failure time and permeability.  
The work gloves' resistance to chemical agents should be checked before use, as it can be unpredictable. The gloves' wear time depends on the duration and type of use.

SKIN PROTECTION

Wear category I professional long-sleeved overalls and safety footwear. Wash body with soap and water after removing protective clothing.

EYE PROTECTION

Wear airtight protective goggles (OSHA 29 CFR 1910.133).

RESPIRATORY PROTECTION

If the threshold value (e.g. TLV-TWA) is exceeded for the substance or one of the substances present in the product, wear a mask with a NIOSH certified filter, whose class must be chosen according to the limit of use concentration (NIOSH 42 CFR 84, OSHA 29 CFR 1910.134). In the presence of gases or vapours of various kinds and/or gases or vapours containing particulate (aerosol sprays, fumes, mists, etc.) combined filters are required.  
Respiratory protection devices must be used if the technical measures adopted are not suitable for restricting the worker's exposure to the threshold values considered. The protection provided by masks is in any case limited.  
If the substance considered is odourless or its olfactory threshold is higher than the corresponding TLV-TWA and in the case of an emergency, wear open-circuit compressed air breathing apparatus or external air-intake breathing apparatus. For a correct choice of respiratory protection device, see standard NIOSH 42 CFR 84, OSHA 29 CFR 1910.134.

ENVIRONMENTAL EXPOSURE CONTROLS

The emissions generated by manufacturing processes, including those generated by ventilation equipment, should be checked to ensure compliance with environmental standards.

9. Physical and chemical properties

9.1. Information on basic physical and chemical properties

|                                  |               |
|----------------------------------|---------------|
| Appearance                       | Not available |
| Colour                           | Not available |
| Odour                            | Not available |
| Odour threshold                  | Not available |
| pH                               | Not available |
| Melting point / freezing point   | Not available |
| Initial boiling point            | Not available |
| Boiling range                    | Not available |
| Flash point                      | > 93 °C       |
| Evaporation Rate                 | Not available |
| Flammability of solids and gases | Not available |
| Lower inflammability limit       | Not available |
| Upper inflammability limit       | Not available |
| Lower explosive limit            | Not available |

**IB03 - Cesium Chloride 1% Cs, Ionization Buffer**

|                                        |               |
|----------------------------------------|---------------|
| Upper explosive limit                  | Not available |
| Vapour pressure                        | Not available |
| Vapour density                         | Not available |
| Relative density                       | 1.01          |
| Solubility                             | Not available |
| Partition coefficient: n-octanol/water | Not available |
| Auto-ignition temperature              | Not available |
| Decomposition temperature              | Not available |
| Viscosity                              | Not available |
| Explosive properties                   | Not available |
| Oxidising properties                   | Not available |

**9.2. Other information**

Information not available

**10. Stability and reactivity****10.1. Reactivity**

There are no particular risks of reaction with other substances in normal conditions of use.

Hydrochloric Acid

Corrodes: metals.

**10.2. Chemical stability**

The product is stable in normal conditions of use and storage.

Hydrochloric Acid

Stable in normal conditions of use and storage.

**10.3. Possibility of hazardous reactions**

No hazardous reactions are foreseeable in normal conditions of use and storage.

Hydrochloric Acid

Develops heat on contact with: amines, aldehydes, permanganates. May form pyrophoric mixtures with: aluminium, fluorine, metals, bases, sulphur compounds. Risk of explosion on contact with: sulphuric acid, alkaline metals.

**10.4. Conditions to avoid**

None in particular. However the usual precautions used for chemical products should be respected.

**10.5. Incompatible materials**

Hydrochloric Acid

Incompatible materials: metals.

## IB03 - Cesium Chloride 1% Cs, Ionization Buffer

**10.6. Hazardous decomposition products**

Information not available

**11. Toxicological information**

In the absence of experimental data for the product itself, health hazards are evaluated according to the properties of the substances it contains, using the criteria specified in the applicable regulation for classification.

It is therefore necessary to take into account the concentration of the individual hazardous substances indicated in section 3, to evaluate the toxicological effects of exposure to the product.

**11.1. Information on toxicological effects**Metabolism, toxicokinetics, mechanism of action and other information

Information not available

Information on likely routes of exposure

Information not available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Information not available

Interactive effects

Information not available

ACUTE TOXICITY

Does not meet the classification criteria for this hazard class

SKIN CORROSION / IRRITATION

Causes skin irritation

SERIOUS EYE DAMAGE / IRRITATION

Causes serious eye irritation

RESPIRATORY OR SKIN SENSITISATION

Does not meet the classification criteria for this hazard class

GERM CELL MUTAGENICITY

Does not meet the classification criteria for this hazard class

CARCINOGENICITY

Does not meet the classification criteria for this hazard class

**IB03 - Cesium Chloride 1% Cs, Ionization Buffer**

Carcinogenicity Assessment:  
7647-01-0Hydrochloric Acid  
IARC:3

**REPRODUCTIVE TOXICITY**

Suspected of damaging fertility or the unborn child

**STOT - SINGLE EXPOSURE**

Does not meet the classification criteria for this hazard class

**STOT - REPEATED EXPOSURE**

Does not meet the classification criteria for this hazard class

**ASPIRATION HAZARD**

Does not meet the classification criteria for this hazard class

**12. Ecological information**

Use this product according to good working practices. Avoid littering. Inform the competent authorities, should the product reach waterways or contaminate soil or vegetation.

**12.1. Toxicity**

Hydrochloric Acid

LC50 - for Fish

282 mg/l/96h *Gambusia affinis* (mosquito fish)

**12.2. Persistence and degradability**

Information not available

**12.3. Bioaccumulative potential**

Information not available

**12.4. Mobility in soil**

Information not available

**12.5. Results of PBT and vPvB assessment**

On the basis of available data, the product does not contain any PBT or vPvB in percentage greater than 0,1%.

**12.6. Other adverse effects**

Information not available



## IB03 - Cesium Chloride 1% Cs, Ionization Buffer

**13. Disposal considerations****13.1. Waste treatment methods**

Reuse, when possible. Neat product residues should be considered special non-hazardous waste.

Disposal must be performed through an authorised waste management firm, in compliance with national and local regulations.

CONTAMINATED PACKAGING

Contaminated packaging must be recovered or disposed of in compliance with national waste management regulations.

**14. Transport information**

The product is not dangerous under current provisions of the Code of International Carriage of Dangerous Goods by Road (ADR) and by Rail (RID), of the International Maritime Dangerous Goods Code (IMDG), and of the International Air Transport Association (IATA) regulations.

**14.1. UN number**

Not applicable

**14.2. UN proper shipping name**

Not applicable

**14.3. Transport hazard class(es)**

Not applicable

**14.4. Packing group**

Not applicable

**14.5. Environmental hazards**

Not applicable

**14.6. Special precautions for user**

Not applicable

## IB03 - Cesium Chloride 1% Cs, Ionization Buffer

## 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Information not relevant

## 15. Regulatory information

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

U.S. Federal RegulationsTSCA:

All components are listed on TSCA Inventory.

Clean Air Act Section 112(b):

7647-01-0

Hydrochloric Acid

Clean Air Act Section 602 Class I Substances:

No component(s) listed.

Clean Air Act Section 602 Class II Substances:

No component(s) listed.

Clean Water Act –  
Priority Pollutants:

No component(s) listed.

Clean Water Act –  
Toxic Pollutants:

No component(s) listed.

DEA List I Chemicals (Precursor Chemicals):

No component(s) listed.

DEA List II Chemicals (Essential Chemicals):EPA List of Lists:

313 Category Code:

7647-01-0

Hydrochloric Acid

7647-01-0

Hydrochloric Acid

EPCRA 302 EHS TPQ:

# EXAXOL CHEMICAL CORPORATION

Revision nr. 1

Dated 9/25/2025

First compilation

Printed on 9/25/2025

Page n. 11/13

## IB03 - Cesium Chloride 1% Cs, Ionization Buffer

No component(s) listed.

EPCRA 304 EHS RQ:

No component(s) listed.

CERCLA RQ:

7647-01-0 Hydrochloric Acid

EPCRA 313 TRI:

7647-01-0 Hydrochloric Acid

RCRA Code:

No component(s) listed.

CAA 112 (r) RMP TQ:

7647-01-0 Hydrochloric Acid

State Regulations

Massachusetts:

7647-01-0 Hydrochloric Acid

Minnesota:

7647-01-0 Hydrochloric Acid

New Jersey:

7647-01-0 Hydrochloric Acid

New York:

7647-01-0 Hydrochloric Acid

Pennsylvania:

7647-01-0 Hydrochloric Acid

California:

7647-01-0 Hydrochloric Acid

Proposition 65:

International Regulations

Substances subject to exportation reporting pursuant to (EC) Reg. 649/2012:

None

Substances subject to the Rotterdam Convention:

None

**IB03 - Cesium Chloride 1% Cs, Ionization Buffer**Substances subject to the Stockholm Convention:

None

Candadian WHMIS

Information not available

**16. Other information**

Text of hazard (H) indications mentioned in section 2-3 of the sheet:

|             |                                                      |
|-------------|------------------------------------------------------|
| <b>H290</b> | May be corrosive to metals.                          |
| <b>H361</b> | Suspected of damaging fertility or the unborn child. |
| <b>H314</b> | Causes severe skin burns and eye damage.             |
| <b>H319</b> | Causes serious eye irritation.                       |
| <b>H315</b> | Causes skin irritation.                              |
| <b>H335</b> | May cause respiratory irritation.                    |

**LEGEND:**

- 313 CATEGORY CODE: Emergency Planning and Community Right-to Know Act Section 313 Category Code
- ADR: European Agreement concerning the carriage of Dangerous goods by Road
- CAA 112 ® RMP TQ: Risk Management Plan Threshold Quantity (Clean Air Act Section 112®)
- CAS NUMBER: Chemical Abstract Service Number
- CE50: Effective concentration (required to induce a 50% effect)
- CERCLA RQ: Reportable Quantity (Comprehensive Environment Response, Compensation, and Liability Act)
- CLP: EC Regulation 1272/2008
- DEA: Drug Enforcement Administration
- EmS: Emergency Schedule
- EPA: US Environmental Protection Agency
- EPCRA: Emergency Planning and Community Right-to Know Act
- EPCRA 302 EHS TPQ: Extremely Hazardous Substance Threshold Planning Quantity (Section 302 Category Code)
- EPCRA 304 EHS RQ: Extremely Hazardous Substance Reportable Quantity (Section 304 Category Code)
- EPCRA 313 TRI: Toxics Release Inventory (Section 313 Category Code)
- GHS: Globally Harmonized System of classification and labeling of chemicals
- IATA DGR: International Air Transport Association Dangerous Goods Regulation
- IC50: Immobilization Concentration 50%
- IMDG: International Maritime Code for dangerous goods
- IMO: International Maritime Organization
- LC50: Lethal Concentration 50%
- LD50: Lethal dose 50%
- OEL: Occupational Exposure Level
- PEL: Predicted exposure level
- RCRA Code: Resource Conservation and Recovery Act Code
- REL: Recommended exposure limit
- RID: Regulation concerning the international transport of dangerous goods by train
- TLV: Threshold Limit Value
- TLV CEILING: Concentration that should not be exceeded during any time of occupational exposure.
- TSCA: Toxic Substances Control Act
- TWA STEL: Short-term exposure limit
- TWA: Time-weighted average exposure limit
- VOC: Volatile organic Compounds
- WHMIS: Workplace Hazardous Materials Information System.

**GENERAL BIBLIOGRAPHY:**

- GHS rev. 3
- The Merck Index. 10th Edition

**IB03 - Cesium Chloride 1% Cs, Ionization Buffer**

- Handling Chemical Safety
- Niosh - Registry of Toxic Effects of Chemical Substances
- INRS - Fiche Toxicologique (toxicological sheet)
- Patty - Industrial Hygiene and Toxicology
- N.I. Sax - Dangerous properties of Industrial Materials-7, 1989 Edition
- ECHA website
- Database of SDS models for chemicals - Ministry of Health and ISS (Istituto Superiore di Sanità) - Italy
- 6 NYCRR part 597
- Cal/OSHA website
- California Safe Drinking Water and Toxic Enforcement Act
- EPA website
- Hazard Communication Standard (HCS 2012)
- IARC website
- List Of Lists EPA: Consolidated List of Chemicals Subject to EPCRA, CERCLA and Section 112® of the Clean Air Act
- Massachusetts 105 CMR Department of public health 670.000: "Right to Know"
- Minnesota Chapter 5206 Department Of Labor and Industry Hazardous Substances, Employee "Right to Know".
- New Jersey Worker and Community Right to know Act N.J.S.A.
- NTP. 2011. Report on Carcinogens, 12th Edition.
- OSHA website
- Pennsylvania, Hazardous Substance List, Chapter 323

**Note for users:**

The information contained in the present sheet are based on our own knowledge on the date of the last version. Users must verify the suitability and thoroughness of provided information according to each specific use of the product.

This document must not be regarded as a guarantee on any specific product property.

The use of this product is not subject to our direct control; therefore, users must, under their own responsibility, comply with the current health and safety laws and regulations. The producer is relieved from any liability arising from improper uses.

Provide appointed staff with adequate training on how to use chemical products.

**Changes to previous review:**

The following sections were modified:

01 / 02 / 03 / 04 / 08 / 09 / 10 / 11 / 12 / 13 / 14 / 16.